





Variety of color options

The Go Chair® is re-engineered from the ground up, offering a bold style available in an array of contemporary colors. Enhanced performance and comfort, along with feather-touch disassembly, allows you to enjoy lightweight travel and independence on the go. With an increased weight capacity of 300 lbs. and a sleek, bold look, the Go Chair® makes travel easy.









Specifications 4-Wheel

Weight Capacity	300 lbs.
Maximum Speed ¹	Up to 3.7 mph
Ground Clearance ³	2" at frame
Turning Radius³	25.5" with foot platform
Overall Length ³	33" with front rigging
Overall Width³	22.5"
Seat-to-Ground Height	22"-23"
Seat-to-Deck Height	16.25"-17.25"
Front Tires	6" solid
Rear Tires	9" solid
Suspension	Limited
Range Per Charge ^{1,2}	Up to 8.7 miles
Total Weight Without Batteries ^{3,7}	67 lbs. (front & rear)
Heaviest Piece When Disassembled ³	36 lbs. (rear)
Standard Seating	Foldable, compact, lightweight 18"x17"
Drive System	N/A
Dual Braking System	N/A
Battery Requirements ^{3,4,5}	(2) 18 AH, 12 V, deep-cycle
Battery Charger	2-amp, off-board

Features

- Choice of 6 colors
- 18" x 17", 5-point swivel seat with latch release
- Improved agility longer wheel base; wider stance
- Compact turning radius 25.4"
- Dual swing-away, under seat storage bins
- Height and width adjustable armrests
- Larger footplate
- One hand feather-touch disassembly
- 60" lap belt
- The heaviest piece is only 36 lbs.

ccessories

- Cup holder
- Lap belt (50", 70")
- Safety flag
- Oxygen tank holder
- Saddlebag
- Weather cover
- Additional battery pack
- Rear mount bracket
- Cane/crutch holder (3" single, 3" double)
- Armrest mount cane clip
- XLR USB charger

Military Patches





Pride offers a variety of lifts to transport your mobility product with ease. To find a compatible lift for your vehicle and mobility product, use our new Lift Finder application at pridemobility.com/lift-finder/

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition tire type and condition. These specifications can be subject to a variance of +10%, -5%.
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
 3 AGM or Gel-Cell type required. *See "Batteries and Charging."
- 4 Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.
- 6 Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA and ISO 7176 series standards. This product is not coded by DME PDAC or does not meet criteria: K0899. All specifications subject to change without notice











GOCHAIR-SS-09-12-17